


GPC-20 series

20W Single Output Switching Power Supply



■ Features:

- Constant current design
- Universal AC input / Full range
- Protections: Short circuit
- Cooling by free air convection
- 100% full load burn-in test
- Isolation class II
- UL1310 Class 2 power unit, pass LPS
- Fully encapsulated with IP67 level

□ IP67 CE LPS

ELECTRICAL SPECIFICATION

MODEL	GPC-20-350		GPC-20-700	
OUTPUT				
NO OUTPUT DC VOLTAGE	50V		30V	
RATED CURRENT	350mA		700mA	
VOLTAGE RANGE	9 ÷ 48V		3 ÷ 28V	
RATED POWER	16.8W		19.6W	
CURRENT ACCURACY	± 5%			
LINE REGULATION	± 1%			
VOLTAGE TOLERANCE [3]	± 5%			
RIPPLE & NOISE (max.) [2]	200mV _{p.p}		200mV _{p.p}	
SETUP, RISE TIME [4]	500ms, 250ms at full load			
HOLD UP TIME (typ.)	24ms / 115VAC, 50ms / 230VAC at full load			
INPUT				
VOLTAGE RANGE	90 ÷ 264VAC			
FREQUENCY RANGE	47 ÷ 63Hz			
EFFICIENCY (typ.)	80%		80%	
AC CURRENT (typ.)	0.55A/115VAC, 0.28A / 230VAC			
INRUSH CURRENT (typ.)	70A / 230VAC			
LEAKAGE CURRENT(max.)	0.25mA / 240VAC			
PROTECTIONS				
SHORT CIRCUIT	Type: hiccup mode, auto-recovery.			
ENVIRONMENT				
WORKING TEMPERATURE	-30°C ÷ 70°C (Refer to Derating Curve)			
WORKING HUMIDITY	20 ÷ 90% RH non-condensing			
STORAGE TEMPERATURE AND HUMIDITY	-40°C ÷ 80°C, 10 ÷ 95% RH non-condensing			
TEMPERATURE COEFFICIENT	± 0.03% / °C (0°C ÷ 50°C)			
VIBRATION	10 ÷ 500Hz, 2G, 10min / cycle, period for 60min. each along X, Y, Z axes			

GPC-20 series

20W Single Output Switching Power Supply



SAFETY & EMC REGULATIONS


SAFETY STANDARDS	Compliance to EN61347-1, EN61347-2-13, IP67
WITHSTAND VOLTAGE	I-P/O-P: 3kVAC
ISOLATION RESISTANCE	I-P/O-P; O-P/FG; I-P/FG: 100M Ω /500VDC/25°C/70%
EMC EMISSION	Compliance to EN55015
EMC IMMUNITY	Compliance to EN61547; EN55024; EN61000-4-2, -3, -4, -5, -6, -8, -11
HARMONIC CURRENT	Compliance to EN61000-3-3; EN61000-3-2

OTHERS


DIMENSIONS	140 x 32 x 25mm
WEIGHT AND PACKING	0.2kg; 100pcs./box; box weight and dimensions: 20kg; 34.5 x 29 x 19.5cm

1. All parameters NOT specially mentioned are measured at 230VAC input, rated load and 25°C of ambient temperature.
2. Ripple & noise are measured at 20MHz of bandwidth by using a 12" twisted pair-wire terminated with a 0.1 μ F i 47 μ F parallel capacitor.
3. Tolerance includes set up tolerance, line regulation and load regulation.
4. Setup and rise time is measured from 0 to 90% rated output voltage.
5. Power supply is considered as a component that will be operated in combination with final equipment. Since EMC performance will be affected by the complete installation, the final equipment must be re-qualify to comply with EMC Directives.

MECHANICAL SPECIFICATION



DERATING CURVE



EU DECLARATION OF CONFORMITY

For the following equipment:

Part No.:	GPC-20-Y (Y = 350, 700)
Batch No.:	GLP17xxxxxxxxxxxxxx

Is herewith confirmed to comply with the requirements set out in the Council Directive, the following standards were applied:

ROHS Directive 2011/65/EU

Low Voltage Directive 2014/35/UE:

Standard	Description
EN 61347-1:2008 + A1:2011 + A2:2013	Lamp controlgear - General and safety requirements.
EN 61347-2-13:2014	Lamp controlgear - Particular requirements for d.c. or a.c. supplied electronic controlgear for LED modules

Electromagnetic Compatibility Directive 2014/30/UE:

Standard	Description
EN55015:2013	Conducted emission / Radiated emission
EN61000-3-2:2014	Harmonic current.
EN61000-3-3:2013	Voltage flicker.
EN61547:2009	Electro-magnetic susceptibility.

Power supply is considered as component of final equipment not intended to apply by end-user. Power supply meets safety and EMC standards however the final equipment with power supply must be re-qualified to comply with EMC and LVD Directives.

MPL POWER ELEKTRO Sp. z o.o.
44-119 Gliwice, ul. Wschodnia 40
NIP 631-24-57-646 REGON 240105606

Company stamp

KIEROWNIK
Działu Technicznego
Łukasz Jaromin

Person signature and stamp